

NAG Library Function Document

nag_dsbgvd (f08ucc)

1 Purpose

nag_dsbgvd (f08ucc) computes all the eigenvalues and, optionally, the eigenvectors of a real generalized symmetric-definite banded eigenproblem, of the form

$$Az = \lambda Bz,$$

where A and B are symmetric and banded, and B is also positive definite. If eigenvectors are desired, it uses a divide-and-conquer algorithm.

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_dsbgvd (Nag_OrderType order, Nag_JobType job, Nag_UploType uplo,
                Integer n, Integer ka, Integer kb, double ab[], Integer pdab, double bb[],
                Integer pddb, double w[], double z[], Integer pdz, NagError *fail)
```

3 Description

The generalized symmetric-definite band problem

$$Az = \lambda Bz$$

is first reduced to a standard band symmetric problem

$$Cx = \lambda x,$$

where C is a symmetric band matrix, using Wilkinson's modification to Crawford's algorithm (see Crawford (1973) and Wilkinson (1977)). The symmetric eigenvalue problem is then solved for the eigenvalues and the eigenvectors, if required, which are then backtransformed to the eigenvectors of the original problem.

The eigenvectors are normalized so that the matrix of eigenvectors, Z , satisfies

$$Z^T A Z = \Lambda \quad \text{and} \quad Z^T B Z = I,$$

where Λ is the diagonal matrix whose diagonal elements are the eigenvalues.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Crawford C R (1973) Reduction of a band-symmetric generalized eigenvalue problem *Comm. ACM* **16** 41–44

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Wilkinson J H (1977) Some recent advances in numerical linear algebra *The State of the Art in Numerical Analysis* (ed D A H Jacobs) Academic Press

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **job** – Nag_JobType *Input*
On entry: indicates whether eigenvectors are computed.
job = Nag_EigVals
 Only eigenvalues are computed.
job = Nag_DoBoth
 Eigenvalues and eigenvectors are computed.
Constraint: **job** = Nag_EigVals or Nag_DoBoth.
- 3: **uplo** – Nag_UploType *Input*
On entry: if **uplo** = Nag_Upper, the upper triangles of A and B are stored.
 If **uplo** = Nag_Lower, the lower triangles of A and B are stored.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 4: **n** – Integer *Input*
On entry: n , the order of the matrices A and B .
Constraint: $n \geq 0$.
- 5: **ka** – Integer *Input*
On entry: if **uplo** = Nag_Upper, the number of superdiagonals, k_a , of the matrix A .
 If **uplo** = Nag_Lower, the number of subdiagonals, k_a , of the matrix A .
Constraint: $ka \geq 0$.
- 6: **kb** – Integer *Input*
On entry: if **uplo** = Nag_Upper, the number of superdiagonals, k_b , of the matrix B .
 If **uplo** = Nag_Lower, the number of subdiagonals, k_b , of the matrix B .
Constraint: $ka \geq kb \geq 0$.
- 7: **ab**[*dim*] – double *Input/Output*
Note: the dimension, *dim*, of the array **ab** must be at least $\max(1, \mathbf{pdab} \times \mathbf{n})$.
On entry: the upper or lower triangle of the n by n symmetric band matrix A .
 This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements of A_{ij} , depends on the **order** and **uplo** arguments as follows:
- if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab**[$k_a + i - j + (j - 1) \times \mathbf{pdab}$], for $j = 1, \dots, n$ and
 $i = \max(1, j - k_a), \dots, j$;
- if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab**[$i - j + (j - 1) \times \mathbf{pdab}$], for $j = 1, \dots, n$ and
 $i = j, \dots, \min(n, j + k_a)$;

if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab** $[j - i + (i - 1) \times \mathbf{pdab}]$, for $i = 1, \dots, n$ and
 $j = i, \dots, \min(n, i + k_a)$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab** $[k_a + j - i + (i - 1) \times \mathbf{pdab}]$, for $i = 1, \dots, n$ and
 $j = \max(1, i - k_a), \dots, i$.

On exit: the contents of **ab** are overwritten.

8: **pdab** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix A in the array **ab**.

Constraint: **pdab** \geq **ka** + 1.

9: **bb** $[dim]$ – double *Input/Output*

Note: the dimension, dim , of the array **bb** must be at least $\max(1, \mathbf{pddb} \times \mathbf{n})$.

On entry: the upper or lower triangle of the n by n symmetric band matrix B .

This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements of B_{ij} , depends on the **order** and **uplo** arguments as follows:

if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 B_{ij} is stored in **bb** $[k_b + i - j + (j - 1) \times \mathbf{pddb}]$, for $j = 1, \dots, n$ and
 $i = \max(1, j - k_b), \dots, j$;
 if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 B_{ij} is stored in **bb** $[i - j + (j - 1) \times \mathbf{pddb}]$, for $j = 1, \dots, n$ and
 $i = j, \dots, \min(n, j + k_b)$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 B_{ij} is stored in **bb** $[j - i + (i - 1) \times \mathbf{pddb}]$, for $i = 1, \dots, n$ and
 $j = i, \dots, \min(n, i + k_b)$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 B_{ij} is stored in **bb** $[k_b + j - i + (i - 1) \times \mathbf{pddb}]$, for $i = 1, \dots, n$ and
 $j = \max(1, i - k_b), \dots, i$.

On exit: the factor S from the split Cholesky factorization $B = S^T S$, as returned by nag_dpbstf (f08ufc).

10: **pddb** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix B in the array **bb**.

Constraint: **pddb** \geq **kb** + 1.

11: **w** $[n]$ – double *Output*

On exit: the eigenvalues in ascending order.

12: **z** $[dim]$ – double *Output*

Note: the dimension, dim , of the array **z** must be at least

$\max(1, \mathbf{pdz} \times \mathbf{n})$ when **job** = Nag_DoBoth;
 1 otherwise.

The (i, j) th element of the matrix Z is stored in

z $[(j - 1) \times \mathbf{pdz} + i - 1]$ when **order** = Nag_ColMajor;
z $[(i - 1) \times \mathbf{pdz} + j - 1]$ when **order** = Nag_RowMajor.

On exit: if **job** = Nag_DoBoth, **z** contains the matrix Z of eigenvectors, with the i th column of Z holding the eigenvector associated with $\mathbf{w}[i - 1]$. The eigenvectors are normalized so that $Z^T B Z = I$.

If **job** = Nag_EigVals, **z** is not referenced.

13: **pdz** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **z**.

Constraints:

if **job** = Nag_DoBoth, **pdz** \geq max(1, **n**);
otherwise **pdz** \geq 1.

14: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_CONVERGENCE

The algorithm failed to converge; $\langle value \rangle$ off-diagonal elements of an intermediate tridiagonal form did not converge to zero.

NE_ENUM_INT_2

On entry, **job** = $\langle value \rangle$, **pdz** = $\langle value \rangle$ and **n** = $\langle value \rangle$.
Constraint: if **job** = Nag_DoBoth, **pdz** \geq max(1, **n**);
otherwise **pdz** \geq 1.

NE_INT

On entry, **ka** = $\langle value \rangle$.
Constraint: **ka** \geq 0.

On entry, **n** = $\langle value \rangle$.
Constraint: **n** \geq 0.

On entry, **pdab** = $\langle value \rangle$.
Constraint: **pdab** $>$ 0.

On entry, **pdbb** = $\langle value \rangle$.
Constraint: **pdbb** $>$ 0.

On entry, **pdz** = $\langle value \rangle$.
Constraint: **pdz** $>$ 0.

NE_INT_2

On entry, **ka** = $\langle value \rangle$ and **kb** = $\langle value \rangle$.
Constraint: **ka** \geq **kb** \geq 0.

On entry, **pdab** = $\langle value \rangle$ and **ka** = $\langle value \rangle$.
Constraint: **pdab** \geq **ka** + 1.

On entry, **pdbb** = $\langle value \rangle$ and **kb** = $\langle value \rangle$.
 Constraint: **pdbb** \geq **kb** + 1.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_MAT_NOT_POS_DEF

If **fail.errnum** = **n** + $\langle value \rangle$, for $1 \leq \langle value \rangle \leq \mathbf{n}$, then nag_dpbstf (f08ufc) returned **fail.errnum** = $\langle value \rangle$: B is not positive definite. The factorization of B could not be completed and no eigenvalues or eigenvectors were computed.

7 Accuracy

If B is ill-conditioned with respect to inversion, then the error bounds for the computed eigenvalues and vectors may be large, although when the diagonal elements of B differ widely in magnitude the eigenvalues and eigenvectors may be less sensitive than the condition of B would suggest. See Section 4.10 of Anderson *et al.* (1999) for details of the error bounds.

8 Further Comments

The total number of floating point operations is proportional to n^3 if **job** = Nag_DoBoth and, assuming that $n \gg k_a$, is approximately proportional to $n^2 k_a$ otherwise.

The complex analogue of this function is nag_zhbgvd (f08uqc).

9 Example

This example finds all the eigenvalues of the generalized band symmetric eigenproblem $Az = \lambda Bz$, where

$$A = \begin{pmatrix} 0.24 & 0.39 & 0.42 & 0 \\ 0.39 & -0.11 & 0.79 & 0.63 \\ 0.42 & 0.79 & -0.25 & 0.48 \\ 0 & 0.63 & 0.48 & -0.03 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 2.07 & 0.95 & 0 & 0 \\ 0.95 & 1.69 & -0.29 & 0 \\ 0 & -0.29 & 0.65 & -0.33 \\ 0 & 0 & -0.33 & 1.17 \end{pmatrix}.$$

9.1 Program Text

```
/* nag_dsbgvd (f08ucc) Example Program.
 *
 * Copyright 2011 Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */

#include <stdio.h>
#include <nag.h>
#include <nagf08.h>
#include <nagx04.h>
#include <nag_stdlib.h>

int main(void)
{

    /* Scalars */
    Integer      exit_status = 0, i, j, ka, kb, n, pdab, pdbb, pdz, zsize;

    /* Arrays */
    double       *ab = 0, *bb = 0, *w = 0, *z = 0;
    char         nag_enum_arg[40];

    /* Nag Types */
    NagError     fail;
```

```

Nag_OrderType order;
Nag_UploType uplo;
Nag_JobType job;

#ifdef NAG_COLUMN_MAJOR
#define AB_UPPER(I, J) ab[(J-1)*pdab + ka + I - J]
#define AB_LOWER(I, J) ab[(J-1)*pdab + I - J]
#define BB_UPPER(I, J) bb[(J-1)*pddb + kb + I - J]
#define BB_LOWER(I, J) bb[(J-1)*pddb + I - J]
    order = Nag_ColMajor;
#else
#define AB_UPPER(I, J) ab[(I-1)*pdab + J - I]
#define AB_LOWER(I, J) ab[(I-1)*pdab + ka + J - I]
#define BB_UPPER(I, J) bb[(I-1)*pddb + J - I]
#define BB_LOWER(I, J) bb[(I-1)*pddb + kb + J - I]
    order = Nag_RowMajor;
#endif

INIT_FAIL(fail);

printf("nag_dsbgvd (f08ucc) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[\n]");
scanf("%ld%ld%ld%*[\n]", &n, &ka, &kb);
if (n < 0 || ka < kb || kb < 0)
{
    printf("Invalid n, ka or kb\n");
    exit_status = 1;
    goto END;
}
scanf(" %s*[\n]", nag_enum_arg);
/* nag_enum_name_to_value(x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
scanf(" %s*[\n]", nag_enum_arg);
job = (Nag_JobType) nag_enum_name_to_value(nag_enum_arg);
if (job==Nag_EigVals) {
    zsize = 1;
    pdz = 1;
} else {
    zsize = n*n;
    pdz = n;
}

pdab = ka + 1;
pddb = kb + 1;
/* Allocate memory */
if (!(ab = NAG_ALLOC((ka+1) * n, double)) ||
    !(bb = NAG_ALLOC((kb+1) * n, double)) ||
    !(z = NAG_ALLOC(zsize, double)) ||
    !(w = NAG_ALLOC(n, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read the triangular parts of the matrices A and B from data file */
if (uplo == Nag_Upper)
{
    for (i = 1; i <= n; ++i)
for (j = i; j <= MIN(i+ka, n); ++j) scanf("%lf", &AB_UPPER(i, j));
    scanf("%*[\n]");
    for (i = 1; i <= n; ++i)
for (j = i; j <= MIN(i+kb, n); ++j) scanf("%lf", &BB_UPPER(i, j));
}
else
{
    for (i = 1; i <= n; ++i)

```

```

for (j = MAX(1, i-ka); j <= i; ++j) scanf("%lf", &AB_LOWER(i, j));
    scanf("%*[\n]");
    for (i = 1; i <= n; ++i)
for (j = MAX(1, i-kb); j <= i; ++j) scanf("%lf", &BB_LOWER(i, j));
    }
scanf("%*[\n]");

/* Solve the generalized symmetric band eigenvalue problem A*x = lambda*B*x
 * using nag_dsbgvd (f08ucc).
 */
nag_dsbgvd(order, job, uplo, n, ka, kb, ab, pdab, bb, pbb, w,
           z, pdz, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dsbgvd (f08ucc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print eigensolution */
printf(" Eigenvalues\n    ");
for (j = 0; j < n; ++j) printf(" %9.4f%s", w[j], j%6 == 5?"\n":" ");
printf("\n");

if (job==Nag_DoBoth) {
    /* nag_gen_real_mat_print (x04cac): Print Matrix of eigenvectors Z. */
    printf("\n");
    fflush(stdout);
    nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, n,
                           z, pdz, "Eigenvectors (by Column)", 0, &fail);
    if (fail.code != NE_NOERROR)
    {
printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
        fail.message);
exit_status = 1;
    }
}

END:
if (ab) NAG_FREE(ab);
if (bb) NAG_FREE(bb);
if (z) NAG_FREE(z);
if (w) NAG_FREE(w);

return exit_status;
}

```

9.2 Program Data

nag_dsbgvd (f08ucc) Example Program Data

```

4      2      1      : n, ka and kb

Nag_Upper      : uplo
Nag_EigVals    : job (Nag_DoBoth for eigenvectors)

0.24   0.39   0.42
      -0.11   0.79   0.63
              -0.25   0.48
              -0.03 : matrix A

2.07   0.95
      1.69  -0.29
              0.65  -0.33
              1.17 : matrix B

```

9.3 Program Results

nag_dsbgvd (f08ucc) Example Program Results

Eigenvalues
-0.8305 -0.6401 0.0992 1.8525
